


Pour and debridge technology

Energy-saving structural thermal barriers for use in aluminum windows, doors, skylights, curtain wall and storefront.



Azon Saves Energy

Azon provides turnkey solutions to the extruder or window manufacturer with complete machinery, thermal barrier chemicals, quality control and service program.

The three-step pour and debridge process results in an energy-saving window frame with the advantage of long-term durability that is warranted from structural deterioration.

How the three-step process works

1. Prepare

An aluminum profile is designed and extruded with a strategically placed cavity to limit the bridge of metal that acts as a conductor of hot or cold temperatures on the exposed surface. The cavity surface is conditioned utilizing either the **Azo-Brader™** or the **Lancer™** machinery devised to produce a mechanical lock prior to the application of the liquid polyurethane polymer into the channel.

2. Pour

The Azon **Fillameter™** with the Tornado III™ dynamic mixer, dispenses liquid two-component polyurethane polymers into the thermal barrier channel. Within minutes, the thermal core solidifies into a very strong, low conductance structural polymer.

3. Debridge

The third and final step in the thermal barrier process is the removal of the metal bridge from the bottom of the channel with the Azon **Bridgemill™**, creating an aluminum-polymer composite with high shear strength capable of withstanding strains and forces in extreme weathering conditions.




Structural thermal barrier polymer

Daylighting systems produced with Azon structural thermal barrier technologies—the **MLP™** or **Dual Cavity**—for aluminum windows and high performance glazing components for insulating glass, will yield a fenestration system capable of upholding the highest efficiency and sustainability standards.

AZO/Tec®

Interdisciplinary team aiding manufacturers with the technical design of structural and energy-efficient fenestration systems by providing a range of design functions and thermal simulation studies.

For more information about thermal barriers, contact the **AZO/Tec®** technical services department azotec@azonusa.com.

AT-A-GLANCE

Performance Products



Industrial Grouts

Since its founding in 1977, Azon has emerged as a world recognized company with international operations on three continents, supplying chemicals and intelligent technologies in most every corner of the globe.

The research and development of patented polyurethane chemistry has also allowed for expansion opportunities into the production of performance chemicals for numerous other industries.



AzoGrout™

Concrete repair

Elastomeric or rigid solid materials for concrete crack, joint, or spall repair


Water control

Hydrophobic polyurethane materials to deflect water and hydrophilic-type urethanes to absorb water, creating a membrane or watertight seal

Soil stabilization

Azo-Grout that encapsulates granules of soil to strengthen and stabilize forming an impermeable barrier

Performance Chemicals



The Azon performance polyurethane polymers have a broad range of application—from flexible foam—to solid cast elastomers used in recreation, food processing, automotive, mass finishing and construction.

With endless capabilities, our MDI-based products include a wide-range of abrasion-resistant polyurethane elastomers suitable for use in dynamic, high abrasion, food-grade handling and anti-static, anti-vibration applications.

Azon produces performance products used in recreation, construction, agriculture, manufacturing, grouting and mass finishing.

Azon
643 W. Crosstown Parkway
Kalamazoo, MI 49008-1910
USA
Tel: 269 385 5942
Fax: 269 373 9295

Azon UK Ltd.
Unit J, St. David's Industrial Estate
Pengam, Blackwood
NP12 3SW
UK
Tel: +44 (0) 1443 878010

Azon Korea Inc.
E1-Space
60-1 Samsung-Dong
Gangnam-Gu, Seoul 135-870
Korea
Tel: + 82 (0) 2 544 5906
Fax: + 82 (0) 2 544 5908

Azon Polyurethane (Shanghai) Co., Ltd.
Room 2804-2807, 28th Floor
Hua Yuan World Square
1958 North Zhongshan Road
Shanghai 200063
PR China
Tel: + 86 (0) 21 6212 2213
Fax: + 86 (0) 21 6211 0004